



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : B60K 15/04, B67D 5/33, 5/14</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/58356</p> <p>(43) International Publication Date: 18 November 1999 (18.11.99)</p>
<p>(21) International Application Number: PCT/IL99/00219</p> <p>(22) International Filing Date: 23 April 1999 (23.04.99)</p> <p>(30) Priority Data: 124424 11 May 1998 (11.05.98) IL</p> <p>(71) Applicant (for all designated States except US): ON TRACK INNOVATIONS LTD. [IL/IL]; Z.H.R. Industrial Zone, P.O. Box 32, 12000 Rosh Pina (IL).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): GILBOA, Ronnie [IL/IL]; Moshav Beit Hillel, 12255 Beit Hillel (IL). BASHAN, Oded [IL/IL]; Charzit Street 24, 21844 Carmiel (IL). ITAY, Nehemya [IL/IL]; Kibbutz Kfar Giladi, 12210 Kfar Giladi (IL). ADUK, Moshe [IL/IL]; Korazim 43, 12391 Korazim (IL).</p> <p>(74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel Aviv (IL).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>
<p>(54) Title: SELF-CLOSING CAP FOR THE FILLING NECK OF A CONTAINER</p>		
<p>(57) Abstract</p> <p>A self-closing cap (50) for the filling neck of a container, the self-closing cap having integral therewith a smart card (54) having a container coil antenna (52) for communicating with a supply station coil antenna fixed to a supply nozzle when the supply nozzle is inserted into the container through the self-closing cap.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

- 1 -

Self-closing cap for the filling neck of a container

FIELD OF THE INVENTION

This invention relates generally to automatic filling of fluid containers, and particularly to refueling of vehicles.

BACKGROUND OF THE INVENTION

5 So-called "Gas Management Systems" (GMS) are known and virtually eliminates the need for a gas station attendant. In such systems, there is mounted around the fuel tank inlet of a vehicle a coil antenna that is controlled by a microcontroller located discreetly within the vehicle. At the refueling site, the nozzle of the GMS system pump is fitted with a nozzle
10 coil front-end which interfaces with the site or forecourt controlling computer.

Authorization to refuel occurs during the contact-free, two-way communication between the vehicle and the site controlling computer. When the pump nozzle enters the fuel inlet, radio frequency communication
15 occurs between the two. Driver identification is also established at this stage providing for an additional level of security.

- 2 -

Where more than one driver uses a specific vehicle, GMS provides an option of issuing driver tags which must be presented to the pump front-end prior placing the nozzle into the fuel inlet. Once the computer is satisfied that this is a authorized driver and that the right fuel is about to be
5 dispensed into the right vehicle, it initiates the flow of fuel into the car's fuel tank.

Refueling continues as long as communication is maintained between the coil antenna in the vehicle's fuel tank and the fuel nozzle. On removing the nozzle, communication is interrupted, immediately stopping
10 the flow of fuel. All data is automatically stored on the site computer and is forwarded daily to the transaction administrators, enabling them to provide their customers with comprehensive fuel management reports.

Installation of such a system requires a mechanical mounting for fixing the coil antenna proximate the fuel tank. The coil antenna must then
15 be wired to the antenna interface of a smart card fitted inside the vehicle thus requiring the steel body of the vehicle to be drilled so as to pass the connection cable therethrough. Whilst these are not in themselves difficult operations, they are clearly beyond the ability of most motorists and thus have to be performed by a mechanic having access to the proper tools.

20 U.S. Patent No. 4,986,439 (Ott *et al.*) discloses a self-closing cap particularly adapted for use with the filler neck of vehicle fuel tanks. As shown in Fig. 1, the self-closing cap 11 comprises a closure ring 15 having an annular seal 23 and being attachable to the filler neck 12. A spring-biased closure flap 14 having a seal is swivel-mounted on the closure ring
25 with two bearing arms 20 to a shaft 30 supported by a bearing block 17 inserted in a recess on the housing ring. A locking spring seated on the shaft of the bearing block biases the closure flap, with one end 29 of the spring

- 3 -

engaging the closure flap 14 or a bearing arm 20 and the other end of the spring engaging the bearing block 17.

When used to seal a vehicle fuel tank, a fuel nozzle being part of a gas filling station may be inserted through the annular seal against the spring bias so as to urge the closure flap into an open position, whereby fuel
5 may be pumped into the fuel tank. On removing the fuel nozzle, the spring biased closure flap returns to its closed position, thus sealing the fuel tank. By such means, no mechanical removal of the seal is required and therefore such a self-closing cap is amenable to automatic fueling systems of the kind
10 described above.

Use of such self-closing caps still does not of itself address the problem associated with mounting the coil antenna around the fuel pipe within the vehicle. It would obviously be desirable if a simpler way were provided for achieving this objective without requiring the services of
15 qualified personnel.

SUMMARY OF THE INVENTION

It is a particular object of the invention to allow a coil antenna to be associated with a vehicle fuel tank in such a manner that drilling of the vehicle body is unnecessary and obviating the need for a special mount.

20 To this end there is provided in accordance with the invention a self-closing cap for the filling neck of a container, the self-closing cap having integral therewith a smart card having a container coil antenna for communicating with a supply station coil antenna fixed to a supply nozzle when the supply nozzle is inserted into the container through the self-closing
25 cap.

- 4 -

Preferably, the container is a vehicle fuel tank and the supply station is a gas station having a complementary coil antenna mounted proximate a fuel nozzle and tuned to the same frequency as the vehicle coil antenna.

BRIEF DESCRIPTION OF THE DRAWINGS

5 In order to understand the invention and to see how it may be carried out in practice, a preferred embodiment will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 is a sectional view of a prior art self-closing cap particularly
10 adapted for use with a vehicle fuel tank;

Fig. 2a is a sectional view showing schematically a detail of a self-closing cap according to the invention having an integral smart card;

Fig. 2b is a detail of Fig. 2a showing in enlarged scale a recess within the self-closing cap for accommodating a smart card and coil antenna;

15 Fig. 3 is a detail of the coil antenna and associated smart card circuit seen in elevation from direction III-III in Fig. 2a.; and

Fig. 4 is a block diagram showing functionally the smart card circuit depicted in Fig. 3.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

20 Figs. 2a and 2b show details of a self-closing cap depicted generally as 50 having a structure similar to that of the device described above with reference to Fig. 1 as described in U.S. Patent No. 4,986,439 which is incorporated herein by reference. The self-closing cap 50 has an outer casing 51 having in a lower surface thereof an annular recess 51. Within the annular
25 recess 51 is wound a coil antenna 52 having one or more turns of wire 53 depending on the particular application for which the coil antenna 52 and

- 5 -

associated electronics are intended. The coil antenna 52 is connected to a smart card depicted generally as 54 which is likewise accommodated within the recess 51.

After mounting the smart card 54 and coil antenna 52 within the recess 51, an epoxy resin is poured into the recess so that, on curing, the smart card 54 and coil antenna 52 are fixedly mounted within the recess 51. As is known, data may be written to the smart card and read therefrom using contactless communication by means of inductive coupling between the coil antenna 52 and another coil antenna (not shown) associated with a smart card reading/writing device. A suitable smart card adapted for bi-directional data communication is described in our U.S. Patent No. 5,241,160 which is incorporated herein by reference.

Fig. 3 is a detail of the coil antenna 52 and associated encapsulated smart card circuit 54 seen in elevation from direction III-III in Fig. 2a having two turns of wire 53, although as noted above the actual number depends on the particular application, being influenced *inter alia* by signal strength, frequency and so on.

Fig. 4 is a block diagram showing functionally the smart card circuit 54 comprising a microprocessor 55 coupled to an antenna interface 56 to which the coil antenna 52 is connected in parallel with a variable capacitor 57 allowing tuning of the smart card tuned circuit to a predetermined working frequency. In order to provide added security, a tamper detector 58 is coupled to the microprocessor 55 for providing a signal thereto in the event that the microprocessor 55 is activated either whilst the self-closing cap 50 is in its closed position; or whilst the self-closing cap 50 is not properly seated on the neck of the fuel tank. Upon receipt of a tamper detection signal, the microprocessor 55 may take suitable pre-programmed action. By such means,

- 6 -

fraudulent use of the self-closing cap 50 and the embedded smart card 54, together with the proprietary data stored therein, may be protected against.

In use, a fuel nozzle (not shown) has mounted in association therewith a coil antenna for generating an electromagnetic field which is inductively
5 coupled to the coil antenna 52 when the fuel nozzle is inserted into a mouth 59 of the self-closing cap 50. By such means, energy is transferred to the smart card 54 for allowing data to be communicated between the smart card 54 and a read/write station coupled to the fuel nozzle and forming part of a Gas Management System.

10 It will be appreciated that variations may be effected to the preferred embodiment without departing from the spirit of the invention. For example, whilst it is preferable to effect energy transfer via inductive coupling for the purpose of powering the smart card circuit 54, a miniature battery 60 may be mounted within the recess for this purpose.

15 The tamper detector 58 may be adapted to operate at different security levels depending on a particular application. For example, if the microprocessor 55 is self-powered when brought within the vicinity of an electromagnetic field, then only on activation will the tamper detection signal be generated. The microprocessor 55 may be programmed to give a suitable
20 warning message and to disable further transactions. If, on the other hand, the microprocessor 55 is powered by means of a battery, the tamper detector can likewise be energized permanently so as to allow total, and optionally irreversible, de-activation of the microprocessor 55. Such total de-activation can be realized in software or in hardware. For example, a self-destructing
25 fuse connecting the power source to the microprocessor 55 can be caused to burn out on detection of the tamper detection signal, thus achieving both total and irreversible de-actuation.

- 7 -

Whilst the mechanical arrangement of the self-closing cap 50 may be as described in U.S. Patent No. 4,986,439, it will be understood that there may be equally well employed any other suitable self-closing cap which allows insertion of the fuel nozzle into the vehicle's fuel tank without
5 requiring manual removal of the cap.

Finally, whilst the invention has been described with particular application to automatic fueling of vehicles, it is apparent that the invention may find general application to the automatic monitoring of fluid control systems. It can be used, for example, for filling central heating fuel tanks by a
10 pre-ordered quantity of fuel whilst allowing the customer to be automatically debited.

- 8 -

CLAIMS:

1. A self-closing cap (50) for the filling neck of a container, the self-closing cap having integral therewith a smart card (54) having a container coil antenna (52) for communicating with a supply station coil antenna fixed
5 to a supply nozzle when the supply nozzle is inserted into the container through the self-closing cap.
2. The self-closing cap according to Claim 1, wherein the container is a vehicle fuel tank and the supply station is a gas station having a complementary coil antenna mounted proximate a fuel nozzle thereof and
10 tuned to the same frequency as the container coil antenna.
3. The self-closing cap according to Claim 1 or 2, wherein the self-closing cap comprises an internal recess (51) for accommodating therein the smart card and the container coil antenna substantially coaxial with the filling neck (59).
- 15 4. The self-closing cap according to Claim 3, wherein the smart card and the container coil antenna are fixedly mounted within the recess by means of a cured epoxy resin.
5. The self-closing cap according to any one of the preceding claims, wherein electrical power is inductively coupled to the smart card upon
20 insertion of the supply nozzle into the container.
6. The self-closing cap according to any one of the preceding claims, including mounting means (52) for mounting therein a battery for supplying electrical power to the smart card.
7. The self-closing cap according to any one of the preceding claims,
25 further including a tamper detection means (58) for producing a tamper detect signal upon attempted fraudulent use of the smart card within the self-closing cap.

- 9 -

8. The self-closing cap according to Claim 7, wherein the tamper detection means is adapted to produce the tamper detect signal if the smart card is activated whilst the self-closing cap is closed.

9. The self-closing cap according to Claim 7, wherein the tamper
5 detection means is adapted to produce the tamper detect signal if the smart card is activated whilst the self-closing cap is not properly seated on the neck of the container.

10. The self-closing cap according to any one of Claims 7 to 9, wherein the smart card is responsive to the tamper detect signal for de-activating
10 totally.

11. The self-closing cap according to Claim 10, wherein the smart card is responsive to the tamper detect signal for de-activating irreversibly.

1/2



FIG. 1
PRIOR ART

FIG. 2A



2/2




FIG. 2B




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

Intr. National Application No.
PCT/IL 99/00219

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B60K15/04 B67D5/33 B67D5/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B60K B67D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 727 608 A (WOODS RONALD ET AL) 17 March 1998 see column 4, line 2 - line 50 see figures 6-8 ---	1,2
A	US 5 605 182 A (OBERRECHT DAVID ET AL) 25 February 1997 see column 2, line 50 - column 3, line 48 see figures ---	1
A	WO 95 14612 A (KELERICH DAVID ; TALMOR DOV (IL); RAPAC NETWORK INT INC (US)) 1 June 1995 & US 5 857 501 A (RAPAC NETWORK INTERNATIONAL INC.) 12 January 1999 see column 1, line 19 - column 2, line 33; claim 1; figures 1,2D,3-5 --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 June 1999

Date of mailing of the international search report

02/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Daehnhardt, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IL 99/00219

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 94 06031 A (CORFITSEN STEN) 17 March 1994 see page 2, line 29 - page 3, line 27; figures ---	1
A	WO 95 32919 A (GUNNARSSON STAFFAN) 7 December 1995 & US 5 862 222 A (GUNNARSSON STAFFAN) 19 January 1999 see column 1, line 60 - column 2, line 17; figures ---	1
A	EP 0 736 484 A (RYAN MICHAEL C) 9 October 1996 see column 4, line 14 - line 29; figure 1 ---	1
A	FR 2 600 318 A (CGA HBS) 24 December 1987 see page 1, line 18 - line 35 -----	1

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/IL 99/00219

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5727608 A	17-03-1998	NONE	
US 5605182 A	25-02-1997	NONE	
WO 9514612 A	01-06-1995	IL 107784 A AU 1396695 A EP 0729426 A US 5857501 A	10-03-1998 13-06-1995 04-09-1996 12-01-1999
WO 9406031 A	17-03-1994	SE 500091 C AT 168199 T AU 4990593 A DE 69319603 D DE 69319603 T EP 0659280 A ES 2118252 T SE 9202550 A US 5671786 A	11-04-1994 15-07-1998 29-03-1994 13-08-1998 11-03-1999 28-06-1995 16-09-1998 05-03-1994 30-09-1997
WO 9532919 A	07-12-1995	EP 0775082 A US 5862222 A	28-05-1997 19-01-1999
EP 0736484 A	09-10-1996	NONE	
FR 2600318 A	24-12-1987	NONE	